



MHOTR242B



17.5" x 24" x 17" (H x W x D)

24" wide over-the-range microwave in black with digital controls, for ducted or recirculating (ductless) use

Highlights:

- 24" wide over-the-range microwave brings new convenience to small kitchens
- Range hood can function with a vertical duct, horizontal duct, or for recirculating operation
- Ten power levels and multi-stage heating ensure the perfect cooking conditions for a variety of meals

Product Features:

24" width	Smartly sized for full service use in smaller kitchens
Range hood function	Under-cabinet ventilation with a high/low setting
Versatile ventilation options	This unit can be set up with a vertical duct, horizontal duct, or for recirculating operation
Large capacity	1.4. cu.ft. interior provides ample room for heating & cooking small or large dishes
Window included	Small window lets you keep watch of your cooking
Under cabinet LED lighting	Range hood includes two bulbs for convenient illumination of the cooking zone
Auto cook	Cooking setting that lets you choose from pizza, potatoes, popcorn, beverages, cheese, ice cream, butter, meats, veggies, and reheat
Kids meal heating option	Designed for easy reheating of common children's meals, with settings specifically for nuggets, hot dogs, fries, and frozen sandwiches
Timed cooking	Touch controls for easy heating of foods and beverages (up to 99 minutes)



The image contains two technical drawings of a rectangular electronic device, showing the front and top views with dimensions in inches.

FRONT VIEW: This view shows the device's profile. The overall width is 14 1/2 inches. The top section has a width of 24 inches and a height of 3 1/2 inches, labeled "3'-4\" L.G. ELEC. CORD". Below this is a "GLASS WINDOW" measuring 11 1/2 inches wide and 5 inches high. The bottom section has a height of 3 3/4 inches and contains a row of eight circular indicators. A "LIMIT" switch is located above the indicators. The total height of the device is 17 1/2 inches. A 10-inch dimension is shown for the distance from the top edge to the start of the indicator row.

TOP VIEW: This view shows the device from above. The overall width is 14 1/2 inches. The depth is 17 inches. Two rectangular components, each 4 inches wide and 2 3/4 inches high, are positioned 2 1/4 inches apart in the center. The distance from the left edge to the first component is 4 3/8 inches. The distance from the right edge to the second component is 1 1/2 inches. The distance from the bottom edge to the components is 14 3/8 inches. An "ELEC. CORD" is shown exiting from the top right corner. The distance from the front edge to the components is 4 3/8 inches.