

G 7516 SCi AutoDos

Semi-integrated dishwasher

with Automatic Dispensing thanks to AutoDos with integrated PowerDisk.



- Innovative design and maximum convenience – 3D MultiFlex Tray
- Communication with an appliance could not be easier – WiFiConn@ct
- Perfect results in less than one hour – QuickIntense Wash
- Perfect illumination for easy loading – BrilliantLight
- All safely loaded where needed – Maxi comfort basket design

EAN: 4002516261520 / Material number: 11388120 / Old Material Number: 21751657USA

Construction type	
Semi-integrated dishwashers	•
Design	
Fascia color	Clean Touch Steel
Fascia panel version	Slanted fascia
Control type	Softkeys
Control panel	1-line text display
Display color	White
MultiLingua	•
Convenience	
Networking with Miele@home	•
Automatic dispensing with PowerDisk	•
Door closing aid	ComfortClose
LED Lighting	•
Operating noise dB(A) re 1 pW	40
Countdown indicator	•
Delay start up to 24 hours	•
In-operation indication	Display
Display language selection	•
Efficiency and sustainability	
EcoFeedback	•
EcoPower Technology	•
Proven hygiene	•
Hot water connection	•
Half load	•
ENERGY STAR® Most Efficient	•
Gentle on dishware/glass	
Fresh water dishwasher	•
AutoOpen drying	•
SensorDry	•
Active condensation drying	•
Perfect GlassCare	•
Dishwashing programs	
QuickIntenseWash	•
Economy	•
Normal	•
SensorWash	•
Pots & Pans	•
IntenseWash	•
China & Crystal	•
SaniWash	•
Extra Quiet	•
Appliance care	•
Rinse & Hold	•
Grates & Filters	•
Rinse options	
AutoDos	•
IntenseZone	•
Express	•
Extra Clean	•

G 7516 SCi AutoDos

Semi-integrated dishwasher

with Automatic Dispensing thanks to AutoDos with integrated PowerDisk.



EAN: 4002516261520 / Material number: 11388120 / Old Material Number: 21751657USA

Extra dry	•
Basket design	
Cutlery loading	3D MultiFlex tray
FlexCare glass holder	4
FlexCare cup rack	2
Basket design	MaxiComfort
Safety	
Waterproof system	•
Check filter saturation indicator	•
Child Safety lock	•
Technical data	
Niche width min in in.(mm)	23 5/8 (600)
Niche width max in in.(mm)	23 5/8 (600)
Niche height min in in.(mm)	33 3/4 (855)
Niche height max in in.(mm)	36 1/4 (920)
Niche depth in in.(mm)	22 1/2 (570)
Appliance width in in.(mm)	23 5/8 (598)
Appliance height in in.(mm)	33 3/4 (855)
Appliance depth in in.(mm)	22 1/2 (570)
Appliance depth with door open in in.(cm)	47 1/2 (120.5)
Net weight in lbs. (kg)	107 (48.2)
Total connected load in kW	1.40
Voltage in V	120
Fuse rating in A	15
Number of phases	1
Electrical frequency standard	60
Length of water inlet hose in ft (m)	5 (1.50)
Length of water drain hose in ft (m)	5 (1.50)
Length of electrical wire in ft (m)	4 (1.20)
Min. front panel weight in kg	3.0
Max. front panel weight in kg	11.0
[can be retrofitted by Service to min.]	6.0
[can be retrofitted by Service to max.]	15.0
Replacing bulbs	Kundendienst
Available display languages	
Available display languages via MultiLingua	deutsch, english, español, français, português,